



ZXIMCU sMesh750

Broadband Mesh Fixed Device



The sMesh ("s" is smart, means highly flexible) broadband ad hoc products, based on LTE, combine mature OFDM technology with flexible channel coding. They feature optimized designs for the physical layer and data link layer, while inheriting the excellent RF (radio frequency) performance of carrier-grade products. This ensures the products' stability, reliability, and adaptability to harsh environments.



Features

- **One Device, Multiple Usages**

Can be fixedly installed outdoors, or mounted on vehicles (ships, aircraft).

It can be flexibly and quickly deployed as needed.

- **Diversified Services**

Support voice, data, positioning, video, etc.

Support VPN transmission, interconnection with systems like satellites, public networks and so on.

- **Flexible Networking**

Ad hoc networking, with flexibly configurable carrier bandwidth.

Support any network topology such as point-to-multipoint, chain relay, mesh, and hybrid structures, as well as multi-hop relaying and forwarding.

- **Easy Management**

With professional dispatching and management tools, it can monitor the working status of devices at each node, wireless link quality in real-time, and view GIS positioning information, etc.

Product Views



Industry Applications



Accessories

Standard



Power Cord (Fixed)



Aviation Plug Network Cable

Optional



Airborne Antenna



Gooseneck Antenna



Air Tube Earphone



Wi-Fi Antenna



GPS Module



HDMI Encoder



USB HD Camera



PAD Dispatch Console



Laptop Dispatch Console



Adapter



Aviation Case



Vehicle-mounted/
Fixed Antenna

Specifications

General	
Frequency	1.4GHz, Other bands customizable
Protocol	TDD
Transmission	COFDM
Bandwidth	1.25MHz/2.5MHz/5MHz/10MHz/20MHz
Transmitting Power	2×2W
Receiving Sensitivity	≤-103dBm
Path	2 paths, 2T2R
Data Rate	≥50Mbps, MIMO≥90Mbps
Networking	Ad hoc network
Ad Hoc Network Maximum Nodes	More than 64 nodes
Hop	Suggest≤9 hops
Encryption	DES/AES256
Physical	
Dimensions	270mm×212mm×110mm (Without handle)
Weight	About 6kg
Port	Network port: data transmission and network management , aviation plug structure Wi-Fi(SMA): connect Wi-Fi antenna RF(N): connect RF antenna GPS: GPS antenna, aviation plug structure Power port: external power supply, aviation plug structure

Electrical	
Power Supply	DC input: 12 - 60V DC, Suggest 48V DC
Environmental Conditions	
Operating Temperature	-40°C~ +60°C
Storage Temperature	-50°C~ +70°C
Air Pressure Range	70 ~ 106 kPa
Dust and Water Resistance	IP67
Seismic Strengthening	GB/T 4798.7-2007 (Part 7: Portable & Non-stationary Use, Above Grade 7M2)
System Extension (Optional)	
Extended Network Access	Support public 4G network, optical port extension
External Video Access	Support HDMI external video access, realize the external video backhaul
Screen	1.7-inch, TFT LCD, show device status, link status, and straight-line distance to adjacent device, etc. Support quick configuration via the screen and buttons

General Disclaimer:
The specifications in this document are in accordance with the applicable standard test.
Due to the continuous technology development, Caltta may change the specifications without prior notice.

Caltta **CALTTA TECHNOLOGIES CO.,LTD.**

Address: 12F/Building G2, International E-City, Nanshan, Shenzhen, China

Web: <https://www.caltta.com/> **E-mail:** sales@caltta.com **Post:** 518052

Privacy Statement: Caltta Technologies is a leading provider of comprehensive critical communication solutions and committed to protecting personal data in accordance with applicable laws and regulations and with technologies including anonymization and data encryption and necessary security management measures.

