

TBS6000M

Integrated DMR Portable Base Station



The TBS6000M Digital Trunking Integrated Base Station adopts a highly integrated design, and features a compact size, portability and high mobility. It supports multiple power supply modes: built-in battery power, AC power, and DC power. With one-touch startup, it enables rapid network deployment. Equipped with a built-in public network backhaul module, it facilitates network establishment and meets the communication requirements of all emergency scenarios.

- Highly Integrated
- Quick Commissioning
- Reliable and Durable
- Versatile Application Scenarios
- Rich Configurations
- Flexible Power Supply
- Compact and Portable
- Public Network Backhaul



Specification

General	
Frequency Range	350MHz: UL: 351~356MHz; DL: 361~366MHz 370MHz: UL: 372~376MHz; DL: 382~386MHz
Channel Spacing	12.5kHz
Protocol	DMR
Duplex Spacing	10MHz
Modulation Rate	9.6kbps
Modulation Scheme	4FSK
Multiple Access Method	TDMA
Carriers	2 Standard Carriers, expandable to 4 carriers

Physical	
Dimensions (H×W×D)	Standard : 362mmx203mmx122mm (With Handle) Equipped Fan: 362mmx203mmx161mm (With Handle) Equipped Battery: 486mmx203mmx122mm (With Handle and Battery)
Weight	Standard: ≤7.5kg Equipped Fan: ≤8.0kg Equipped Battery: ≤10kg
Power Supply	DC 10.8V~15V (External power adapter supports 220V AC and -48V DC)
Power Consumption	≤ 80W@2x5W ≤105W@2x10W
Battery Runtime	More than 4 hours
Operating Temperature	-40°C ~ +55°C
Storage Temperature	-50°C ~ +85°C
Operating humidity	5% ~ 95%
Dust and Water Resistance	IP67
Seismic Resistance	GB/T 4798.5 7M2
Transmission Immunity	ETSI EN 300 386/ ETSI TS 125 113

Transmitter	
Single Carrier RF Power	Low Power: ≤ 5W High Power: ≤ 10W
Frequency Stability	0.05ppm
Adjacent Channel Power Ratio (ACPR)	≤-60 dB (±12.5KHz) ≤-70 dB (±25KHz)
Spurious Emission	≤-36dBm@100KHz (9KHz~1GHz) ≤-30dBm@1MHz (1GHz~12.75GHz)

Receiver	
Static Sensitivity	≤ -121dBm@BER 5%
Blocking	≥96 dB
Adjacent Channel Selectivity	≥60 dB
Co-channel Suppression	≥-12dB
Intermodulation Response Suppression (IMRS)	≥70dB
Spurious Response Immunity	≥70dB
Spurious Emission	≤-57dBm@100KHz (9KHz~1GHz) ≤-47dBm@1MHz (1GHz~12.75GHz)

Reliability	
Mean Time Between Failures (MTBF)	≥250,000 hours
Mean Time To Repair (MTTR)	1 hour

General Disclaimer:
The specifications in this document are in accordance with the applicable standard test. Due to the continuous technology development, Caltta may change the specifications without prior notice.

Caltta **CALTTA TECHNOLOGIES CO.,LTD.**

Address: 12F/Building G2, International E-City, Nanshan, Shenzhen, China

Web: <https://en.caltta.com/> **E-mail:** sales@caltta.com **Post:** 518052

Privacy Statement: Caltta Technologies is a leading provider of comprehensive critical communication solutions and committed to protecting personal data in accordance with applicable laws and regulations and with technologies including anonymization and data encryption and necessary security management measures.

